# **Specification Sheet**

## JA7500 VPXi— UV Lamp head Power Supply



UV lamp Power supply designed to interface with the JA7500 series of lamp heads, offering variable power and system integration input and output facilities. Primary output is rated for a continuous 6kW maximum and supplied in a rugged case suitable for industrial applications.

#### Control Interface - Touch Screen control

- Display both Target and Actual Level.
- Three power levels, standby, level 1 & Pulse (level 2)
- Easy set up of target lamp output between 25-100%.
- Read Lamp Run Hours.
- Configuration Menu adjustment of tolerance (for OK signal , pulse time and level).
- See both set and actual levels.

#### **Control Interface (Inputs)**

- E-Stop Contact Closure (24Vdc closure indicates system is safe).
- Remote Start (Pulse for 300mS will start the lamp if estop and remote stop input closed)
- Remote Stop (Open for 300mS will stop the lamp Note priority to stop over start). Must be made if not used.
- Remote Power control (24Vdc closure indicates power to be set remotely).
- Remote Power control input (0-10Vdc = 30 100% output).
- Pulse mode active (Pulse for 300mS will cause output to increase or decrease too set level)

### Interface Features.

- Remote E-Stop
- Remote Start Stop.
- Pulse Mode





Jenton International Limited 9/10 Ardglen Industrial Estate, Evingar Road, Whitchurch, HAMPSHIRE RG28 7BB UNITED KINGDOM

Tel:+44 (0)1256 892194

Web www.jenton.co.uk

# Technical Specification.



## Physical Layout

	185mm
<340mm	<pre>650mm allow 690mm Including connectors</pre>

Note additional clearance is required for ventilation.

Electrical Supply		Output	
Voltage Supply	380- 415Vac – 3 Phase (3P+N+E)	Lamp Power	400V
Phase Loading	15Amps (at 100%) - Ph-Ph	Max Lamp Power	5000 Watts
	2 Amps Ph– Neutral	Aux Fan Drive	24Vdc 3 5 Amps
Termination	Supplied with Red 32A - 5 wire plug.		

## Control Features.

•	Start button		0
•	Three user settable power levels	SET POWER	
		STANDBY POWER1	POWER 2 EXT STOP
•	Indicates power level set (appears when running).		-999 %
•	Indicates actual power level achieved.	ACTUAL POW	ER 999 %
		-9999 W Limit	
•	Bulb status – on or off – also pressing here will show		
	lamp hours.		
•	Configuration Menu.		

**Product Order Code** Power Supply —JA5000VPXI-0000 Recommended Lamp Head - 3706-0000



UNITED KINGDOM Tel:+44 (0)1256 892194

Jenton International Limited

Web www.jenton.co.uk