



Jenton Banding
Excellence in packaging automation



StraPack Akebono OB-360N

semi-automatic banding machine

The new generation OB-360N is more than just a new name. The upgraded OB-360, has been re-designed to facilitate maintenance, to be more efficient and easier to operate.

FEATURES & BENEFITS

High Speed

Up to 30 cycles per minute. Soft or elastic bundles can be banded without sacrificing the speed.

Versatile

Applies banding to packages as small as 30mm wide x 10mm high, up to 420mm wide x 210mm high. Either paper or film tape can be used. Larger arch sizes available upon request

Impeccable Sealing

Sealing Design eliminates curling, folded or peeling of tape edges.

Wide Tension Range Available

Tension can be selected from 5N to 60N using a simple dial.

Easy Maintenance

A tape shooter attachment guide and built-in aluminum sealing frame have been added, making the OB-360N simple to assemble and easy to maintain.

Simple Operation

- The machine can be operated by simply placing a pack on the table (photocell detection), pressing the Start Button or stepping on the Foot Pedal.
- Reset function to quickly return to the starting position.
- Safety function: the machine doesn't operate unless a package has been placed on the table.

Arch Size	W 435 mm x H 200 mm	
Dimensions	Width	570 mm
	Depth	282 mm
	Height	489 mm
	Weight	25.5 kg
Table Height	238 mm	
Min Package Size	W 30 mm x H 10 mm	
Max Package Size	W 420 mm x H 210 mm	
Tape	Paper - W 30 mm x 190m 80g, Film - W 30mm x 200 - 370m 60 - 110µm	
Strap Tension	60µm Film 5-30N (0.5-3 kgf) 110µm Film 5-60N (0.5-6.1kgf) 80g (28oz.) Paper 5-45N (0.5-4.6kgf)	
Power Supply	200-240 V 1 Phase 50 / 60 Hz	



Optional Large Reel Dispenser W570mm x D456mm x H1105mm, Table Ht. 854mm, Wt. 58.5k

Contact us to find out more and discuss your requirements



Jenton Banding
Excellence in packaging automation

+44 (0) 1256 892194 | sales@jenton.co.uk
www.jentonbanding.co.uk