




Jenton Banding
Excellence in packaging automation



StraPack Akebono OB-560N

semi-automatic tape banding machine

- High Speed - Up to 25 cycles/ minute
- Impeccable sealing technology
- Versatile - 50mm banding, either paper or film tape
- Adjustable Tension – From 5 to 30N

Like the new generation OB-360N, the OB-560N has been designed to facilitate maintenance, to be more efficient and easier to operate. It runs 50mm wide paper and film as opposed to 30mm on the OB-360N.

FEATURES & BENEFITS

High Speed

Up to 25 cycles per minute. Soft or elastic bundles can be banded without sacrificing the speed.

Versatile

Applies banding to packages as small as 30mm wide x 10mm high, up to 420mm wide x 210mm high. Either paper or film tape can be used. Larger arch sizes available upon request.

Impeccable Sealing

Sealing design eliminates curling, folded or peeling of tape edges.

Simple Operation

- The machine can be operated by simply placing a pack on the table (photocell detection), pressing the Start Button or stepping on the Foot Pedal.
- Reset function to quickly return to the starting position.
- Safety function: the machine doesn't operate unless a package has been placed on the table.

Easy Maintenance

A tape shooter attachment guide and built-in aluminum sealing frame have been added, making the OB-560N simple to assemble and easy to maintain.

Wide Tension Range Available

Tension can be selected from 5N to 30N using a simple dial.

Arch Size	W 425 mm x H 220 mm	
Dimensions	Width	570 mm
	Depth	342 mm
	Height	490 mm
	Weight	27.5 kg
Table Height	238 mm	
Min Package Size	W 30 mm x H 10 mm	
Max Package Size	W 420 mm x H 210 mm	
Tape	Paper - W 50 mm x 190m 80g Film-W 50mm x 200-370mm 60-110µm	
Strap Tension	5-30N (0.5-3kgf) adjustable	
Power Supply	200-240 V 1 Phase 50 / 60 Hz	

Contact us to find out more and discuss your requirements



Jenton Banding
Excellence in packaging automation

+44 (0) 1256 892194 | sales@jenton.co.uk
www.jentonbanding.co.uk