



US-3000 AD 360x260 to 500x500 30 mm
The leading banding machine for every need

A

Tech Specs

Weight net	115 kg ¹
Pallet size for shipment (Length x Width x Height)	120x80x160 cm (for 1-2 Machines)
Working height	860-1035 mm
Color	ATS standard
Pneumatic connection	6 bar (only for arch air)
Display languages	cs, da, de, en, es, fi, fr, it, nl, no, pl, pt, sv

Features

- ✓ Adjustable 5-inch touchscreen with intuitive operation and assistance
- ✓ Software update via USB stick
- ✓ Intelligent door concept for easy maintenance and operation
- ✓ Quick belt change with an innovative dispenser concept
- ✓ IIoT-Ready

Basic package

Nr.	Mechanical build
<input type="checkbox"/>	Arch size 360x260 mm (650006)
<input type="checkbox"/>	Arch size 360x360 mm (650007)
<input type="checkbox"/>	Arch size 500x360 mm (650008)
<input type="checkbox"/>	Arch size 500x500 mm (650015)

Nr.	Electrical build
<input type="checkbox"/>	Connection 200-240 V ~ 50-60 Hz
<input type="checkbox"/>	Connection 100-120 V ~ 50-60 Hz

Options

Nr.	Mechanical options
119F1	<input type="checkbox"/> Print mark reader
151F1	<input type="checkbox"/> Sonotrode 30 mm neutral
155F1	<input type="checkbox"/> Air supported arch ²

Nr.	Electrical options

Max. cycle time / min³

Arch	Min. Product ⁴	Max. Product ⁵
360x260	24	30
360x360	23	29
500x360	21	27
500x500	19	26

Additional equipment

Nr.	Equipment
✓	Foot pedal

¹ Weight of the base package (without additional options) with arch size 360x260

² Air supported arch option is included in base package at arch 500x500

³ With ideal infeeding and machine settings

⁴ Dimension minimum product circumference = 100 mm

⁵ Dimension maximum product circumference generally 20 mm distance from arch

Layout example US-3000 AD 360x260/30mm

