



**US-3000 AD 360x260 to 500x500 50 mm**  
The leading banding machine for every need

**A**

**Tech Specs**

Weight net	115 kg <sup>1</sup>
Pallet size for shipment (Length x Width x Height)	120x80x160 cm (for 1-2 Machines)
Working height	860-1035 mm
Color	ATS standard
Pneumatic connection	6 bar (only for arch air)
Display languages	cs, da, de, en, es, fi, fr, it, nl, no, pl, pt, sv

**Features**

- ✓ Adjustable 5-inch touchscreen with intuitive operation and assistance
- ✓ Software update via USB stick
- ✓ Intelligent door concept for easy maintenance and operation
- ✓ Quick belt change with an innovative dispenser concept
- ✓ IIoT-Ready

**Basic package**

Nr.	Mechanical build
<input type="checkbox"/>	Arch size 360x260 mm (650010)
<input type="checkbox"/>	Arch size 360x360 mm (650011)
<input type="checkbox"/>	Arch size 500x360 mm (650012)
<input type="checkbox"/>	Arch size 500x500 mm (650016)

Nr.	Electrical build
<input type="checkbox"/>	Connection 200-240 V ~ 50-60 Hz
<input type="checkbox"/>	Connection 100-120 V ~ 50-60 Hz

**Options**

Nr.	Mechanical options
119F1	<input type="checkbox"/> Print mark reader
150F0	<input type="checkbox"/> Sonotrode 41 mm with ATS logo
150F1	<input type="checkbox"/> Sonotrode 41 mm neutral
151F1	<input type="checkbox"/> Sonotrode 30 mm neutral
155F1	<input type="checkbox"/> Air supported arch <sup>2</sup>

Nr.	Electrical options

**Max. cycle time / min<sup>3</sup>**

Arch	Min. Product <sup>4</sup>	Max. Product <sup>5</sup>
360x260	24	30
360x360	23	29
500x360	21	27
500x500	19	26

**Additional equipment**

Nr.	Equipment
✓	Foot pedal

<sup>1</sup> Weight of the base package (without additional options) with arch size 360x260

<sup>2</sup> Air supported arch option is included in base package at arch 500x500

<sup>3</sup> With ideal infeeding and machine settings

<sup>4</sup> Dimension minimum product circumference = 100 mm

<sup>5</sup> Dimension maximum product circumference generally 20 mm distance from arch

# Layout example US-3000 500x360/50mm

